


Figure 3






Figure 4




Figure 5

Figure 6




Figure 7





Figure 8 (a)



```

<?xml version="1.0" encoding="UTF-8"?>
<application usecookies="false" id="{F6681A6F-FB7C-4901-855C-0S791DDE8DC8}"
  securevariables="false">
  <description version="1" name="MQBanking" />
  <outtargets />
  <startform totargetid="UserID" />
  <subapps />
  <errortarget totargetid="UserID" />
  <properties>
    <variable default="209.23.23.23" name="ServerIP" />
  </properties>
  <sessionvariables>
    <variable name="Session" />
  </sessionvariables>
  <forms>
    <form targetid="UserID" includeheaders="false">
      <stylesheet contenttype="WML11" url="http://www.mobileq.com" />
      <action totargetid="Password" name="OK" />
      <inputvariables />
      <outputvariables>
        <variable name="UserID" />
      </outputvariables>
      <events />
    </form>
    <form targetid="Password" includeheaders="false">
      <stylesheet contenttype="WML11" url="http://www.mobileq.com" />
      <action totargetid="Main" name="OK" />
      <inputvariables>
        <variable name="UserID" />
      </inputvariables>
      <outputvariables>
        <variable name="Session" />
      </outputvariables>
      <events />
    </form>
    <form targetid="Main" includeheaders="false">
      <stylesheet contenttype="WML11" url="http://www.mobileq.com" />
      <action totargetid="Account" name="Account Balance" />
      <action totargetid="Bill Payment" name="Bill Payment" />
      <action totargetid="Transfer" name="Account Transfer" />
      <inputvariables />
      <outputvariables />
      <events />
    </form>
    <form targetid="Account" includeheaders="false">
      <stylesheet contenttype="WML11" url="http://www.mobileq.com" />
      <action totargetid="Details" name="OK" />
      <inputvariables />
      <outputvariables>
        <variable name="AccountID" />
      </outputvariables>
    </form>
  </forms>
</application>

```

Figure 8(b)

```

    <events />
  </form>
  <form targetid="Details" includeheaders="false">
    <stylesheet contenttype="WML11" url="http://www.mobilleq.com" />
    <action totargetid="Main" name="OK" />
    <inputvariables>
      <variable name="AccountID" />
    </inputvariables>
    <outputvariables />
    <events />
  </form>
  <form targetid="Bill Payment" includeheaders="false">
    <stylesheet contenttype="WML11" url="http://www.mobilleq.com" />
    <action totargetid="Bill" name="OK" />
    <inputvariables />
    <outputvariables>
      <variable name="AccountID" />
    </outputvariables>
    <events />
  </form>
  <form targetid="Bill" includeheaders="false">
    <stylesheet contenttype="WML11" url="http://www.mobilleq.com" />
    <action totargetid="Amount" name="OK" />
    <inputvariables>
      <variable name="AccountID" />
    </inputvariables>
    <outputvariables>
      <variable name="BillID" />
      <variable name="AccountID" />
    </outputvariables>
    <events />
  </form>
  <form targetid="Amount" includeheaders="false">
    <stylesheet contenttype="WML11" url="http://www.mobilleq.com" />
    <action totargetid="Confirm" name="OK" />
    <inputvariables>
      <variable name="BillID" />
      <variable name="AccountID" />
    </inputvariables>
    <outputvariables>
      <variable name="AccountID" />
      <variable name="BillID" />
      <variable name="Amount" />
    </outputvariables>
    <events />
  </form>
  <form targetid="Confirm" includeheaders="false">
    <stylesheet contenttype="WML11" url="http://www.mobilleq.com" />
    <action totargetid="Main" name="Cancel" />
    <inputvariables>
      <variable name="AccountID" />
      <variable name="BillID" />
    </inputvariables>
  </form>

```

Figure 8(c)

```

        <variable name= "Amount" />
    </inputvariables>
    <outputvariables>
        <variable name="AccountID" />
        <variable name="BillID" />
        <variable name="Amount" />
    </outputvariables>
    <events />
</form>
</forms>
<errors />
<events />
</application>

```

Figure 8(d)

```

</xml>
<dataresults>
  <data name="source1">
    <RECORDS>
      <RECORD>
        <Blair PK="1">172-32-1176</Blair>
        <Test1 PK="1">1</Test1>
        <Test2 PK="1">2</Test2>
        <Test3 PK="1">3</Test3>
        <LastName>White</LastName>
        <FirstName>Johnson</FirstName>
      </RECORD>
      <RECORD>
        <Blair PK="1">213-46-891</Blair>
        <Test1 PK="1">1</Test1>
        <Test2 PK="1">2</Test2>
        <Test3 PK="1">3</Test3>
        <LastName>Green</LastName>
        <FirstName>Marjorie</FirstName>
      </RECORD>
      <RECORD>
        <Blair PK="1">238-95-7766</Blair>
        <Test1 PK="1">1</Test1>
        <Test2 PK="1">2</Test2>
        <Test3 PK="1">3</Test3>
        <LastName>Carson</LastName>
        <FirstName>Cheryl</FirstName>
      </RECORD>
    </a>
    <RECORD>
      <Blair PK="1">238-95-7766</Blair>
      <Test1 PK="1">1</Test1>
      <Test2 PK="1">2</Test2>
      <Test3 PK="1">3</Test3>
      <LastName>Carson</LastName>
      <FirstName>Cheryl</FirstName>
    </RECORD>
  </a>
  <b>
    <RECORD>
      <Blair PK="1">238-95-7766</Blair>
      <Test1 PK="1">1</Test1>
      <Test2 PK="1">2</Test2>
      <Test3 PK="1">3</Test3>
      <LastName>Carson</LastName>
      <FirstName>Cheryl</FirstName>
    </RECORD>
  </b>
</a>
</RECORDS>

```

Figure 9(a)

```

</data>
<data name="source2">
  <RECORDS>
    <RECORD>
      <Blair PK="1">aaaaaa</Blair>
      <Test1 PK="1">1</Test1>
      <Test2 PK="1">2</Test2>
      <Test3 PK="1">3</Test3>
      <LastName>White</LastName>
      <FirstName>Johnson</FirstName>
    </RECORD>
    <RECORD>
      <Blair PK="1">bbbbbbb</Blair>
      <Test1 PK="1">1</Test1>
      <Test2 PK="1">2</Test2>
      <Test3 PK="1">3</Test3>
      <LastName>Green</LastName>
      <FirstName>Marjorie</FirstName>
    </RECORD>
    <RECORD>
      <Blair PK="1">cccccc</Blair>
      <Test1 PK="1">1</Test1>
      <Test2 PK="1">2</Test2>
      <Test3 PK="1">3</Test3>
      <LastName>Carson</LastName>
      <FirstName>Cheryl</FirstName>
    </RECORD>
    <a>
      <RECORD>
        <Blair PK="1">ddddddd</Blair>
        <Test1 PK="1">1</Test1>
        <Test2 PK="1">2</Test2>
        <Test3 PK="1">3</Test3>
        <LastName>Carson</LastName>
        <FirstName>Cheryl</FirstName>
      </RECORD>
    </a>
    <a>
      <b>
        <RECORD>
          <Blair PK="1">eeeeeeee</Blair>
          <Test1 PK="1">1</Test1>
          <Test2 PK="1">2</Test2>
          <Test3 PK="1">3</Test3>
          <LastName>Carson</LastName>
          <FirstName>Cheryl</FirstName>
        </RECORD>
      </b>
    </a>
  </RECORDS>
</data>
</dataresults>

```

Figure 9(b)

```

<actions>
  <action formatstring="" actionid="OK" querystring="?
    _SQRSIGN=A&_SQAPPID={B77444A1-8D9E-4248-A664-
    6C483F8B4540}&_ACTIONID=OK&_SQFORMID={8D7B4336-6341-
    4D2C-82D8-49FE88D1B13A}&EmployeeID=$EmployeeID" />
</actions>
<dictionary>
  <variable />
  <variable />
</dictionary>
</rml>

```

Figure 9(c)

```

<xsl:stylesheet xmlns:xsl="http://www.w3.org/TR/WD-xsl">
- <xsl:template match="/">
-   <wml>
-     <head>
-       <meta name="FormType" content="SQSelectForm" />
-       <meta name="ListMethod" content="numeric" />
-     </head>
-     <card>
-       <xsl:attribute name="title">qwe</xsl:attribute>
-     <p>
-       <select>
-         <xsl:attribute name="title">qwe</xsl:attribute>
-         <xsl:attribute name="name">asd</xsl:attribute>
-         <xsl:for-each select="/rml/dataresults/data
-           [@name='source2']//RECORD">
-           <option>
-             <xsl:attribute name="value">
-               <xsl:value-of select="Blair" />
-               z1z
-               <xsl:value-of select="Test1" />
-               z1z
-               <xsl:value-of select="Test2" />
-               z1z
-               <xsl:value-of select="Test3" />
-             </xsl:attribute>
-             <xsl:attribute name="title">
-               <xsl:value-of select="LastName" />
-               '
-               <xsl:value-of select="FirstName" />
-               '
-               <xsl:value-of select="/rml/data
-                 [@name='source1']/RECORDS/RECORD/Blair" />
-             </xsl:attribute>
-             blah blah blah
-           </option>
-         </xsl:for-each>
-       </select>
-     </p>
-     <xsl:for-each select="/rml/actions//action">
-     <do>
-       <xsl:attribute name="type">accept</xsl:attribute>
-       <xsl:attribute name="label">
-         <xsl:value-of select="@actionid" />
-       </xsl:attribute>
-     <go>
-       <xsl:attribute name="href">
-         <xsl:value-of select="@querystring" />
-       </xsl:attribute>
-     </go>
-     </do>
-   </xsl:for-each>
- </card>

```

Figure 10(a)

```
</wml>
</xsl:template>
<xsl:stylesheet>
```

```
<xsl:stylesheet xmlns:xsl="http://www.w3.org/1999/XSL/Transform" version="1.0">
  <xsl:output method="text"/>
  <xsl:template match="/">
    <xsl:element name="wml" namespace="http://www.wapforum.org/wml11/">
      <xsl:element name="card" namespace="http://www.wapforum.org/wml11/">
        <xsl:element name="title" namespace="http://www.wapforum.org/wml11/">Title</xsl:element>
        <xsl:element name="text" namespace="http://www.wapforum.org/wml11/">Text</xsl:element>
      </xsl:element>
    </xsl:element>
  </xsl:template>
</xsl:stylesheet>
```

Figure 10(b)

```

<wml>
  <head>
    <meta name="FormType" content="SQSelectForm" />
    <meta name="ListMethod" content="numeric" />
  </head>
  <card title="Select Account">
    <p>
      <select title="Select Account" name="HoldingsAccountID">
        <option value="1" title="Acct 10314">Acct 10314</option>
        <option value="2" title="Acct 11345">Acct 11345</option>
      </select>
      <br />
    </p>
    <do type="accept" label="OK">
      <go href="?"_SQRSIGN=A&_SQAPPID={8D3608DF-E570-45E9-BEC1-
        4E5DD949C5C0}&_ACTIONID=OK&_SQFORMID={BCC091A1-63D4-
        11D3-9E34-0090273EFC3B}
        &HoldingsAccountID=${HoldingsAccountID}
        &UserID=246531&Session=1" />
    </do>
  </card>
</wml>

```

Figure 11

Figure 12

Error

A very bad error happened

OK